

CABLE & POWER SUPPLY COMPATIBILITY CHART

	POWER SUPPLY	DEVICE POWER CABLE	TC2-8-R2 (Molex to 3M)	TC5-8-R2 (3M to SATA)	DEVICE SIGNAL CABLE	TC3-8 (SATA)	TC6-2, TC6-8 (IDE)	DEVICE CABLE COMBO	TC3-22-18 (SATA)	TC4-8 (SAS/SATA)	TC4-8-R2 (SAS/SATA)	TC4-20-R2 (SAS/SATA)	FIREWIRE CABLE	TC7-9-9, TCA7-4-9, TCA7-6-9	USB CABLE	TC8	TC-USB3, TC-USB3-18	PCIe CABLE	TC-PCIe-4, TC-PCIe-8, TC-PCIe-20
Portable Forensic Bridges																			
Tableau PCIe Bridge [T7u]																			
Tableau SAS Bridge [T6u]																			
Tableau USB 3.0 Bridge [T8u]		TP5 or TP2																	
Tableau SATA/IDE Bridge [T35u & T35u-RW]																			
Tableau FireWire Bridge [T9]																			
Integrated Forensic Bridges																			
Tableau Universal Bridge [T356789iu] *1, 2		Dual SATA																	
Tableau SATA Imaging Bay [T3iu] *1, 3		SATA																	
Forensic Duplicators																			
Tableau Duplicator [TD2u]																			
Tableau Imager [TD3]		TP5																	

*1 - Guidance Software does not provide host connection cables for the Tableau Integrated Forensic Bridges as the customer or integrator will typically select a custom cable with the proper length and Host USB 3.0 connection types.

*2 - A USB 3.0 cable to the host computer motherboard or controller is required.

*3 - No device cables are required.